



CTA Products Group

6915 Crumpler Blvd.

Suite B #130

Olive Branch, MS 38654

Phone: 901-647-6909

Toll Free: 877-536-1446

Email: Sales@ChemTch.com

Outlast™ Deck Seal

Semi-transparent Stain Concentrate

Available in Three Beautiful Wood Tones

Original Golden Toner—Red Maple Toner—Walnut Toner

Outlast **Deck Seal** Semi-transparent stain Concentrate has been formulated specifically for preserving the functionality and beauty of exterior wood surfaces. **Deck Seal** is the perfect blend of resins, waterproofing agents, UV inhibitors, and semi-transparent iron oxides in a base designed to stop the unsightly graying of wood even as it brings a halt to the warps, checks, and splits of unprotected wood swelling and shrinking under the influence of rain and sun. **Deck Seal** leaves a beautifully tinted, hydrophobically modified surface that resists the growth of mold and mildew without obscuring the grain of the wood. Your decks, fences, and wood furniture will look as good as new.

Directions: Never apply Outlast **Deck Seal** without dilution. Always dilute with four parts by volume of Mineral Spirits or neutral oil if you reside in an area where VOC limitations restrict the use of mineral spirits. **If using Outlast Deck Oil Conditioner as a pre-treatment, always wait 2 weeks before top coating with this product.** Otherwise, proceed as follows:

1. Prepare the wood for treatment by cleaning thoroughly with a product such as CTA's Restore™ or Oxo Wood Cleaner. Use a low-pressure washer to remove deposits of mold and mildew. Allow the wood to dry.
2. Dilute Outlast **Deck Seal** with four volumes of Mineral Spirits or neutral oil for every volume of concentrate used. (For example: One gallon of concentrate could be poured into a five-gallon bucket and then filled to the fill-line with Mineral Spirits.)
3. Mix thoroughly. It is important that product be completely mixed with the solvent. Use of a mixing blade on a hand drill or similar apparatus is recommended.
4. Pour the diluted **Deck Seal** into a pump-up sprayer or other suitable application equipment.
5. Spray the surface in broad strokes, making sure that all surfaces are sufficiently wet from the product. Normal coverage rate is about 200 square feet per gallon.
6. Although **Deck Seal** will not settle in its concentrated state, it may settle after dilution. Large tanks of diluted material should be fitted with a means of agitation. Small containers should be periodically shaken during application.
7. If desired, a second coat of mineral spirits diluted **Deck Seal** may be applied within three to six hours depending on the heat and humidity. If using neutral oil, wait 24 hours.
8. Allow to dry overnight before walking on decks or using wood furniture.

Warning: May cause eye irritation. Avoid contact with eyes. **FIRST AID:** In case of contact, immediately flush with water for at least 15 minutes. Get medical attention if irritation persists. Please refer to the MSDS for more specific safety information.

KEEP OUT OF REACH OF CHILDREN.

For spill, leak, or Medical Emergency call Infotrac 800-535-5053